



MATERIAL SAFETY DATA SHEET

BAYER CORPORATION
PRODUCT SAFETY & REGULATORY AFFAIRS
100 Bayer Road
Pittsburgh, PA 15205-9741

TRANSPORTATION EMERGENCY
CALL CHEMTREC: 800-424-9300
INTERNATIONAL: 703-527-3887

NON-TRANSPORTATION
BAYER EMERGENCY PHONE...: (412) 923-1800
BAYER INFORMATION PHONE.: (800) 662-2927

1. CHEMICAL PRODUCT IDENTIFICATION:

PRODUCT NAME.....: Makrolon 2558 2405 2407 2408 2458 2805 2807 2858 3258 6555
PRODUCT NAME.....: 6557 GF8001 GF8002 GF9002 ET3113 ET3117 Rx1805
PRODUCT NAME.....: SF800 SF805 SF810
OLD COLOR NO.....: 1000
PRODUCT CODE.....: J5901000
CHEMICAL FAMILY.....: Thermoplastic Polymer
CHEMICAL NAME.....: Bisphenol A Polycarbonate
FORMULA.....: Not applicable - polymeric material

2. COMPOSITION/INFORMATION ON INGREDIENTS:

INGREDIENT NAME /CAS NUMBER EXPOSURE LIMITS CONCENTRATION (%)

\*\*\*\*\* HAZARDOUS INGREDIENTS \*\*\*\*\*

This product contains no hazardous ingredients as defined under the criteria of the Federal OSHA Hazard Communication standard 29 CFR 1910.1200.

3. HAZARDS IDENTIFICATION:

\*\*\*\*\*
\* EMERGENCY OVERVIEW \*
\* CAUTION! Color: Natural; Form: Pellets; Odor: Slight; \*
\* Causes a slipping hazard if spilled; Contact with hot \*
\* material will cause thermal burns; Toxic gases/fumes are \*
\* given off during burning or thermal decomposition; Melted \*
\* product is flammable and produces intense heat and dense \*
\* smoke during burning. \*
\*\*\*\*\*

3. HAZARDS IDENTIFICATION (Continued)

POTENTIAL HEALTH EFFECTS:

ROUTE(S) OF ENTRY.....: Inhalation; Skin Contact; Eye Contact

HUMAN EFFECTS AND SYMPTOMS OF OVEREXPOSURE:

ACUTE EFFECTS OF EXPOSURE.....: Material is a non-reactive solid. Mechanical irritation (i.e. abrasion) to the eyes may occur due to exposure to fines. Eyes may become red and scratchy and may tear. NOTE: Gases and fumes evolved during the thermal processing or decomposition of this material may irritate the eyes, skin or respiratory tract. At recommended processing conditions, the primary fume constituents evolved are water, carbon dioxide (CO<sub>2</sub>), diphenyl carbonate, and monochlorobenzene.

CHRONIC EFFECTS OF EXPOSURE...: None known

CARCINOGENICITY

NTP.....: Not listed as a carcinogen  
IARC.....: Not listed as a carcinogen  
OSHA.....: Not listed as a carcinogen

MEDICAL CONDITIONS

AGGRAVATED BY EXPOSURE.....: None known

EXPOSURE LIMITS.....: For product fines, the OSHA-PEL for nuisance dust of 15 mg/m<sup>3</sup> total dust, 5 mg/m<sup>3</sup> respirable dust is recommended. In addition, the ACGIH-TLV for Particulates Not Otherwise Classified (PNOC) of 10 mg/m<sup>3</sup> is recommended. Observe a more stringent limit for product fines if applicable. Refer to section 2 for any other applicable exposure limits.

At temperatures above decomposition (716 F (380 C)), phenol and other chemicals listed in the hazardous decomposition products can be generated. (See section 10) Care should be taken to observe the exposure limits and minimize exposure to these components if the product is heated to the decomposition temperature. The ACGIH-TLV and OSHA-PEL for phenol is 5 ppm-TWA

4. FIRST AID MEASURES:

FIRST AID FOR EYES.....: Flush eyes with plenty of lukewarm water. See a physician or ophthalmologist for followup if irritation is present and persists.

FIRST AID FOR SKIN.....: Wash affected areas with soap and water. See a physician if thermal burn occurs.

FIRST AID FOR INHALATION: Move to an area free from risk of further exposure. Give oxygen or artificial respiration as needed (to be administered by authorized medical personnel only.) Obtain medical attention.

4. FIRST AID MEASURES (Continued)

FIRST AID FOR INGESTION.: If material is ingested, do not induce vomiting.  
Contact a physician.

5. FIRE FIGHTING MEASURES:

FLASH POINT.....: Above 842 F (450 C) ASTM D-1929B

FLAMMABLE LIMITS:

UPPER EXPLOSIVE LIMIT (UEL)(%): Not established

LOWER EXPLOSIVE LIMIT (LEL)(%): Not established

AUTO-IGNITION TEMPERATURE.....: Above 842 F (450 C) ASTM D-1929B

EXTINGUISHING MEDIA.....: Water; Carbon Dioxide; Dry Chemical; Foam

SPECIAL FIRE FIGHTING PROCEDURES: Full emergency equipment with self-contained breathing apparatus must be worn by firefighters.

UNUSUAL FIRE / EXPLOSION HAZARDS: During a fire, irritating and toxic gases and aerosols may be generated by thermal decomposition and combustion (see Section 10). Dust from flaked material or secondary operations (regrinding, etc.) may form explosive mixtures in air. Vent storage bins, conveyors, dust collectors, etc. (See Section 7.)

6. ACCIDENTAL RELEASE MEASURES:

SPILL OR LEAK PROCEDURES.....: If molten material is spilled, allow it to solidify. For both solidified material and pellets, remove mechanically by a method which minimizes the generation of airborne dust and place in appropriately marked containers.

7. HANDLING and STORAGE:

STORAGE TEMPERATURE(MIN/MAX): Max 200 F (93 C)

SHELF LIFE.....: Not established

SPECIAL SENSITIVITY.....: Moisture

HANDLING/STORAGE PRECAUTIONS: When handling flaked material or during secondary operations, vent storage bins, conveyors, dust collectors, etc. Ground handling equipment. Keep open flames, sparks and heat away from dusty areas. Maintain highest standards of housekeeping to prevent accumulation of dust.

OTHER NOTES.....: Material should be stored in a clean, dry environment in sealed containers. Material must be dried before processing.

-----  
8. PERSONAL PROTECTION:  
-----

EYE PROTECTION REQUIREMENTS.....: Safety glasses are recommended as a good industrial hygiene and safety practice.

SKIN PROTECTION REQUIREMENTS.....: None required but fabric gloves are recommended when handling molten material.

VENTILATION REQUIREMENTS.....: Provide natural or mechanical ventilation to control exposure levels below airborne exposure limits (If indicated in Section 2 or 3). Local mechanical exhaust ventilation should be used at sources of air contamination, such as open process equipment, or during purging operations, to capture gases and fumes that may be emitted. Standard reference sources regarding industrial ventilation (i.e. ACGIH Industrial Ventilation) should be consulted for guidance about adequate ventilation. In the event of thermal decomposition from overheating the product (decomposition begins at 716 F (380)), evacuate the work area, shut down equipment, and provide general ventilation to the room prior to reoccupying.

RESPIRATOR REQUIREMENTS.....: NIOSH/MSHA-approved dust respirator recommended if the airborne dust concentration is near or exceeds the nuisance dust exposure limits.

ADDITIONAL PROTECTIVE MEASURES.....: The greatest potential for injury occurs when working with molten polymeric resins, such as during a purge of a molding machine, extruder and the like. During this type of operation it is essential that all workers in the immediate area wear eye protection and skin protection (sleeves, gloves, etc.) as protection from thermal burns. Purgings should be collected as small flat thin shapes or thin strands to allow for rapid cooling. Precautions should be taken against auto-ignition of hot, thick masses of the plastic. Quench with water. Grinder dust is an exposure hazard.

-----  
9. PHYSICAL and CHEMICAL PROPERTIES:  
-----

PHYSICAL FORM.....: Pellets

COLOR.....: Natural

ODOR.....: Slight

pH.....: Not applicable

BOILING POINT.....: Not applicable

MELTING/FREEZING POINT....: 428-446 F (220-230 C)

SOFTENING POINT.....: 302-320 F (150-160 C)

SOLUBILITY IN WATER.....: Insoluble

SPECIFIC GRAVITY.....: Approx. 1.2

BULK DENSITY.....: 38-42 lb/cuft

% VOLATILE BY VOLUME.....: Negligible

EVAPORATION RATE.....: Not applicable (Butyl acetate = 1)

VAPOR PRESSURE.....: Not applicable

VAPOR DENSITY.....: Not applicable (Air = 1)

-----  
10. STABILITY and REACTIVITY:  
-----

STABILITY.....: This is a stable material  
HAZARDOUS POLYMERIZATION...: Will not occur.  
INCOMPATIBILITIES.....: None known  
INSTABILITY CONDITIONS.....: None known  
DECOMPOSITION TEMPERATURE...: Begins at 716 F (380 C)  
DECOMPOSITION PRODUCTS.....: By fire or thermal decomposition: Carbon monoxide (CO), carbon dioxide (CO2), Bisphenol A, diphenyl carbonate, phenol and phenol derivatives. Traces of aliphatic and aromatic hydrocarbons, aldehydes and acids may also be formed.

-----  
11. TOXICOLOGICAL INFORMATION:  
-----

TOXICITY DATA FOR: Bisphenol A Polycarbonate

ACUTE TOXICITY

OTHER ACUTE EFFECTS: Gases and fumes evolved during thermal decomposition of similar products have caused respiratory irritation in mice.\*

\* Toxicologic evaluation of thermoplastic resins at and above processing temperature, G.K. Sangha, M. Matijak and Y. Alarie, Department of Industrial Environmental Health Sciences, Graduate School of Public Health, University of Pittsburgh, Pittsburgh, PA, 15216, AIHA Journal (42), July 1981.

-----  
12. ECOLOGICAL INFORMATION:  
-----

NO ECOLOGICAL INFORMATION AVAILABLE

-----  
13. DISPOSAL CONSIDERATIONS  
-----

WASTE DISPOSAL METHOD.....: Material may be incinerated or landfilled in compliance with federal, state and local environmental control regulations.

-----  
14. TRANSPORTATION INFORMATION:  
-----

TECHNICAL SHIPPING NAME.....: Bisphenol A Polycarbonate  
FREIGHT CLASS BULK.....: Plastic Materials, Pellets

14. TRANSPORTATION INFORMATION (Continued)

-----  
FREIGHT CLASS PACKAGE.....: Plastic Materials, O/T Exp., Pellets  
PRODUCT LABEL.....: Makrolon All 000000

DOT (DOMESTIC SURFACE)  
-----

HAZARD CLASS OR DIVISION .....: Non-Regulated

IMO / IMDG CODE (OCEAN)  
-----

HAZARD CLASS DIVISION NUMBER...: Non-Regulated

ICAO / IATA (AIR)  
-----

HAZARD CLASS DIVISION NUMBER...: Non-Regulated

-----  
15. REGULATORY INFORMATION:  
-----

OSHA STATUS.....: This product is not hazardous under the criteria  
of the Federal OSHA Hazard Communication Standard  
29 CFR 1910.1200. However, thermal processing  
and decomposition fumes from this product may be  
hazardous as noted in Section 3.

CERCLA REPORTABLE QUANTITY...: None reported

SARA TITLE III:

SECTION 302 EXTREMELY HAZARDOUS SUBSTANCES:

None

SECTION 311/312

HAZARD CATEGORIES.....: Non-hazardous under Section 311/312

SECTION 313 TOXIC CHEMICALS:

None

RCRA STATUS.....: If discarded in its purchased form, this product  
would not be a hazardous waste either by listing or by characteristic.  
However, under RCRA, it is the responsibility of the product user to  
determine at the time of disposal, whether a material containing the  
product or derived from the product should be classified as a hazardous  
waste. (40 CFR 261.20-24)

CHEMICAL INVENTORY LIST(S)

UNITED STATES TSCA STATUS...: On TSCA Inventory

15. REGULATORY INFORMATION (Continued)

The following chemicals are specifically listed by individual states; other product specific health and safety data in other sections of the MSDS may also be applicable for state requirements. For details on your regulatory requirements you should contact the appropriate agency in your state.

COMPONENT NAME /CAS NUMBER	CONCENTRATION	STATE CODE
Bisphenol A Polycarbonate 25971-63-5	>1.0%	NJ4, PA3
Bisphenol A Polycarbonate NJTSRN (31765300002)-8136P	as needed	NJ4, PA3
Residual Methylene Chloride 75-09-2	< 3 ppm	CA1, MA1

CA1 = This chemical is known to the state of California to cause cancer.  
MA1 = Massachusetts Hazardous Substance List  
NJ4 = New Jersey Other - included in 5 predominant ingredients > 1%  
NJTSRN = New Jersey Trade Secret Registry Number  
PA3 = Pennsylvania Non-hazardous present at 3% or greater.

Additional types of polycarbonate covered by New Jersey Trade Secret Registry Number 31765300002-8136P may be used as necessary to adjust the melt flow rate.

16. OTHER INFORMATION:

HMIS RATINGS:                   Health    Flammability    Reactivity  
                                  0            1                    0  
                                  0=Minimal 1=Slight 2=Moderate 3=Serious 4=Severe

Bayer's method of hazard communication is comprised of Product Labels and Material Safety Data Sheets. HMIS ratings are provided by Bayer as a customer service.

REASON FOR ISSUE.....: Name change for color harmonization.  
PREPARED BY.....: P. E. Malichky  
APPROVED BY.....: J. H. Chapman  
APPROVAL DATE.....: 08/27/2001  
SUPERSEDES DATE.....: 07/22/2001  
MSDS NUMBER.....: 11508

-----  
This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Bayer Corporation. The data on this sheet relates only to the specific material designated herein. Bayer Corporation assumes no legal responsibility for use or reliance upon these data.  
-----

Product Code: J5901000  
Approval date: 08/27/2001

MSDS Page 8  
Last page